

Auxiliary
Equipment

Recycling
Systems

Printing
Systems

Blown Film
Lines



Discover the World of Professional Extrusion

Blown Film Machine SH-DF40/45PEW80(A/B/A)



shouman-machinery.com



8 El-Gaish Street
El-Mansoura, Egypt
Tel. : +2(0)50 2 300 200
Fax : +2(0)50 2 300 600



SHOUMAN
M A C H I N E R Y



SH-DF40/45PEW80 (A/B/A)

Technical Specifications

Model	SH-DF40/45PEW80 (A/B/A)		
Machine Type	Three layer blown film machine type (A/B/A)		
Resin Type	LDPE - HDPE - LLPE- Caco ₃ filler		
Lay Flat Film Width	Up to 750 mm		
Film Thickness Range	0.012 mm - 0.2 mm Depends on material		
Extrusion Capacity	Up to 90 kg/hr		
Extruder Design	1 X Φ 40 mm - 1 X Φ 45 mm Highly wear resistant alloy steel with special heat treatments water cooled feeding zone and optimized screw design,with hard chrome plating		
Control / operator interface	Separate cabinet type integrating temperature control system indicators, and operator input instruments		
Total Heating Capacity	28.5 kW		
Dimensions	Length	4750 mm	
	Width	3000 mm	
	Height	4250 mm adjustable	

8 El-Gaish Street
El-Mansoura, Egypt

Tel. : +2(0)50 2 300 200
Fax : +2(0)50 2 300 600

shouman-machinery.com

