

Auxiliary
Equipment

Recycling
Systems

Printing
Systems

Blown Film
Lines



SHOUMAN
M A C H I N E R Y



Discover the World of Professional Extrusion

Blown Film Machine SH-SF32/SH-SF40



shouman-machinery.com



8 El-Gaish Street
El-Mansoura, Egypt

Tel. : +2(0)50 2 300 200
Fax : +2(0)50 2 300 600



SHOUMAN
M A C H I N E R Y



SH-SF32/SH-SF40

Technical Specifications

Model	SH-SF32PEW45	SH-SF40PEW60
Machine Type	Mono-layer blown film machine	
Resin Type	LDPE - HDPE - LLPE	
Lay Flat Film Width	Up to 400 mm	Up to 550 mm
Film Thickness Range	0.007 mm - 0.1 mm Depends on material	0.007 mm - 0.15 mm Depends on material
Extrusion Capacity	Up to 25 kg/hr	Up to 40 kg/hr
Extruder Design	1 X Φ 32 mm Highly wear resistant alloy steel with special heat treatments water cooled feeding zone and optimized screw design, with hard chrome plating	1 X Φ 40 mm
Control / operator interface	Separate cabinet type integrating temperature control system indicators, and operator input instruments	
Total Heating Capacity	8 kW	9.1 kW
Dimensions	Length	2000 mm
	Width	1500 mm
	Height	2750 mm
		2500 mm
		2000 mm
		Up to 3250 mm (adjustable height)

8 El-Gaish Street
El-Mansoura, Egypt

Tel. : +2(0)50 2 300 200
Fax : +2(0)50 2 300 600

shouman-machinery.com

