

Auxiliary
Equipment

Recycling
Systems

Printing
Systems

Blown Film
Lines



Discover the World of Professional Extrusion

Blown Film Machine SH-SF65/SF80



shouman-machinery.com



8 El-Gaish Street
El-Mansoura, Egypt
Tel. : +2(0)50 2 300 200
Fax : +2(0)50 2 300 600



SHOUMAN
M A C H I N E R Y



SH-SF65/SH-SF80PE

Technical Specifications

Model	SH-SF65PEW130	SH-SF80PEW220	
Machine Type	Mono-layer blown film machine		
Resin Type	LDPE - HDPE - LLPE	LDPE - LLPE	
Lay Flat Film Width	Up to 1250 mm	Up to 2150 mm	
Film Thickness Range	0.02mm - 0.25 mm Depends on material	0.60 mm - 0.22 mm Depends on material	
Extrusion Capacity	Up to 150kg/hr	Up to 220kg/hr	
Extruder Design	1 X Φ 65 mm Highly wear resistant alloy steel with special heat treatments water cooled feeding zone and optimized screw design, with hard chrome plating	1 X Φ 80 mm	
Control / operator interface	Separate cabinet type integrating temperature control system indicators, and operator input instruments		
Total Heating Capacity	22 kW	28 kW	
Dimensions	Length	7000 mm	9000 mm
	Width	3000 mm	6000 mm
	Height	7000 mm	10000 mm

8 El-Gaish Street
El-Mansoura, Egypt

Tel. : +2(0)50 2 300 200
Fax : +2(0)50 2 300 600

shouman-machinery.com

